

# CX50, CX60, CX70, CX80, CX90 and CX100 Tractors

## Service Manual Don 7-71427

### Table of Contents

	Section	Pub. No.
<b>1 GENERAL</b>		
Loctite Product Chart		8-98902
How it Works .....	1	7-70810
Safety Rules, General Information and Torque Specifications.....	1001	8-86531
General Specifications and Torques .....	1002	7-71854
Special Tools .....	1005	7-71865
<b>2 ENGINE</b>		
How it Works .....	2	7-70820
Engine Removal and Installation .....	2001	7-73780
<b>NOTE: For Service and Overhaul procedures refer to your Engine Service Manual 7-71721.</b>		
<b>3 FUEL SYSTEM</b>		
Fuel Tank Removal and Servicing.....	3005	7-72610
<b>NOTE: For Service and Overhaul procedures refer to your Engine Service Manual 7-71721.</b>		
<b>4 ELECTRICAL</b>		
How it Works and Electrical Schematics .....	4001	7-70200
Instrument Cluster Programming and Troubleshooting.....	4002	7-71332
Battery Servicing and Testing.....	4004	7-73210
<b>5 STEERING</b>		
Steering Column and Hand Pump.....	5001	7-72042
2WD Steering Cylinder .....	5002	7-71291
2WD Front Axle .....	5003	7-72001
<b>6 TRANSMISSION</b>		
How it Works .....	6	7-70830
Separating the Tractor (between Engine and Speed Transmission).....	6001	7-71890
Engine Clutch and Master Cylinder .....	6002	7-71900
Powershift and Forward/Reverse		
Transmission Servicing .....	6003	7-71921
Creep Transmission Servicing.....	6004	7-73490
8 Speed Transmission Servicing .....	6005	7-71270
Synchronizer Speed Transmission Servicing .....	6006	7-71930
Range Transmission Servicing (2WD) .....	6008	7-73740
Range Transmission Servicing (MFD).....	6009	7-71791
Rear Axles .....	6010	7-71110

... continued

**NOTE:** Information contained in this Manual may cover features that are not available in all markets worldwide.

**CASE CORPORATION**  
700 State Street  
Racine, WI 53404 U.S.A.

**CASE CANADA CORPORATION**  
3350 South Service Road  
Burlington, ON L7N 3M6 CANADA

Don 7-71437

Copyright © 2000 Case Corporation  
Printed in U.S.A.  
February 1998 (Revised October 2000)

MFD Transfer Gearbox, Drive Shaft and Parking Brake .....	6011	7-71310
Differential .....	6012	7-71120
Differential - from Transmission Serial Number JKA412637 and Creep Transmissions .....	6012	7-73760
PTO .....	6013	7-71130
Shiftable PTO .....	6014	7-71150
Front PTO .....	6015	7-71170
MFD Axle - up to Axle Serial Number 37835 .....	6021	7-39121
MFD Axle - from Axle Serial Number 37836 .....	6021	7-71190
<b>7 BRAKES</b>		
How it Works .....	7	7-70840
Service Brakes and Master Cylinder .....	7001	7-73770
Parking Brake (2WD) .....	7002	7-70970
Hydraulic Trailer Brake .....	7004	7-73750
<b>8 HYDRAULICS (see note ** for this section)</b>		
How it Works .....	8	7-70850
How to Read Symbols in a Hydraulic Schematic .....	8000	8-94372
Hydraulic Troubleshooting and Schematic .....	8001	7-71951
Filter Manifold and Main Hydraulic Pump .....	8002	7-71960
Steering Hydraulic Pump .....	8003	7-70980
Regulator Valve .....	8004	7-72030
Differential Lock Cylinder and Solenoid .....	8005	7-71660
Unloading Valve .....	8006	7-71670
Remote Valves .....	8007	7-71680
Hitch Valve and EDC Manifold .....	8009	7-71971
Hydraulic Housing and Lift Cylinder .....	8010	7-71370
Front Hitch .....	8011	7-71690
<b>9 CHASSIS AND MOUNTED EQUIPMENT</b>		
Pedal, Lever and Switch Adjustments .....	9001	7-72054
Air Conditioner System Component Servicing .....	9005	7-70740
Cab Removal and Tilting the Cab Roof .....	9006	7-71990
Cab Mountings .....	9008	7-73470
<b>9 CONTROLLER SYSTEMS</b>		
Calibration, Error Codes, Troubleshooting and Schematics (Tractors not equipped with Ride Control) .....	10002	7-74440
Calibration, Error Codes, Troubleshooting and Schematics (Tractors equipped with Ride Control) .....	10002	7-74450
Programming the Hitch/MFD/Differential Lock Controller .....	10010	7-74350

**NOTE \*\***

Please include section 8008 (7-71980) in this manual.

# LOCTITE PRODUCT CHART

Product	Color	Similar Products	Gap (In Inches)	Strength (Steel/Steel)	Working Temperature Range-Fahrenheit	Fixture/Full Cure (Steel/Steel) Time	Primer	Description
#3	Dark Brown					24 hr	N/A	Form a Gasket (works with oil, fuel or grease) Pliable
80	Yellow					Fast	N/A	Weatherstrip Adhesive
123	Clear					N/A	N/A	Parts Cleaner Fluid
220	Blue	290	0.003	57/143 in lbs	-65 to +250	6 min/24 hrs	747	Wicking Threadlocker
221	Purple	222	0.005	75/44 in lbs	-65 to +300	2 min/24 hrs	747	Low Strength Threadlocker
222	Purple		0.005	53/30 in lbs	-65 to +300	20 min/24 hrs	764	Low Strength Threadlocker (Small Screws)
225	Brown	222	0.010	45/25 in lbs	-65 to +300	7 min/24 hrs	747	Low Strength Threadlocker
242	Blue		0.005	80/50 in lbs	-65 to +300	10 min/24 hrs	764	Medium Strength Threadlocker
262	Red	271	0.005	160/190 in lbs	-65 to +300	5 min/24 hrs	747	High Strength Threadlocker
270	Green	271	0.007	160/320 in lbs	-65 to +300	3 min/24 hrs	747	High Strength Threadlocker
271	Red	262	0.007	160/320 in lbs	-65 to +300	10 min/24 hrs	764	High Strength Threadlocker
272	Red	620	0.007	180/220 in lbs	-65 to +450	30 min/24 hrs	764	High Temperature, High Strength
275	Green	277	0.010	210/300 in lbs	-65 to +300	3 min/24 hrs	747	High Strength Threadlocker
277	Red		0.010	225/300 in lbs	-65 to +300	60 min/24 hrs	764	High Strength Threadlocker
290	Green		0.003	85/350 in lbs	-65 to +300	6 min/24 hrs	764	Wicking Threadlocker
*404	Clear	495	0.006	3200 psi	-65 to +180	30 sec/24 hrs	NA	Instant Adhesive
*406	Clear		0.004	3200 psi	-65 to +180	15 sec/24 hrs	N/A	Surface Insensitive Adhesive
*409	Clear	454	0.008	2500 psi	-65 to +180	50 sec/24 hrs	N/A	Gel Instant Adhesive
*414	Clear		0.006	2500 psi	-65 to +180	30 sec/24 hr	N/A	Instant Adhesive
*415	Clear	454	0.010	2500 psi	-65 to +180	50 sec/24 hrs	N/A	Gap Filling Instant Adhesive (Metals)
*416	Clear	454	0.010	2500 psi	-65 to +180	50 sec/24 hrs	N/A	Gap Filling Instant Adhesive (Plastics)
*420	Clear		0.002	2500 psi	-65 to +180	15 sec/24 hrs	N/A	Wicking Instant Adhesive
*422	Clear	454	0.020	2800 psi	-65 to +180	60 sec/24 hrs	N/A	Gap Filling Instant Adhesive
*430	Clear		0.005	2500 psi	-65 to +180	20 sec/24 hrs	N/A	Metal Bonding Adhesive
*445	White/Black		0.250	2000 psi	-65 to +180	5 min/24 hrs	N/A	Fast Setting 2 Part Epoxy
*454	Clear		0.010	3200 psi	-65 to +180	15 sec/24 hrs	N/A	Surface Insensitive Gen Instant Adhesive
*495	Clear		0.004	2500 psi	-65 to +180	20 sec/24 hrs	N/A	General Purpose Instant Adhesive
*496	Clear		0.005	2500 psi	-65 to +180	20 sec/24 hrs	N/A	Metal Bonding Adhesive
504	Brt Orange	515	0.030	750 psi	-65 to +300	90 min/24 hrs	None	Rigid Gasket Eliminator
509	Light Blue		0.020	750 psi	-65 to +320	6 hr/72 hrs	764	Flange Sealant
510	Red		0.020	1000 psi	-65 to +400	30 min/24 hrs	764	High Temperature, Gasket Eliminator
515	Purple		0.010	750 psi	-65 to +300	1 hr/24 hrs	764	Gasket Eliminator 515

Rac 8-98902

\* Products 404-496 (except for #445) are all instant adhesives (super glues) they differ mostly in viscosity

Printed in U.S.A.

# LOCTITE PRODUCT CHART

Product	Color	Similar Products	Gap (In Inches)	Strength (Steel/Steel)	Working Temperature Range-Fahrenheit	Fixture/Full Cure (Steel/Steel) Time	Primer	Description
518	Red	515	0.030	500psi	-65 to +300	1 hr/24 hrs	764	Gasket Eliminator 518 for Aluminum
542	Brown	569	N/A	132/92 in lbs	-65 to +300	2 hr/24 hrs	747	Hydraulic Sealant
545	Purple		N/A	25/20 in lbs	-65 to +300	4 hr/24 hrs	747	Low Strength Pneumatic/Hydraulic Sealant
549	Orange	504	0.020	2500 psi	-65 to +300	2 hr/24 hrs	747	Instant Seal Plastic Gasket
554	Red	277	0.015	240/240 in lbs	-65 to +300	2 to 4 hrs/24 hrs	764	Refrigerant Sealant
567	White	592	N/A	500 psi	-65 to +400	4 hrs/24 hrs	764	Pipe Sealant for Stainless Steel
568	Orange	277	0.015	2500 psi	-65 to +300	12 hrs/24 hrs	764	Plastic Gasket
569	Brown	545	0.010	40/25 in lbs	-65 to +300	1 hr/24 hrs	764	Hydraulic Sealant
570	Brown	592	N/A	25/40 in lbs	-65 to +300	6 hrs/72 hrs	764	Steam Sealant
571	Brown	592	0.015	40/20 in lbs	-65 to +300	2 to 4 hrs/24 hrs	764	Pipe Sealant
572	White	578.575	N/A	80/27 in lbs	-65 to +300	24 hrs/72 hrs	None	Gasketing
592	White		0.020	500 psi	-65 to +400	4 hrs/72 hrs	736	Pipe Sealant with Teflon
593	Black		0.250	400 psi	-95 to +400	30 min/24 hrs	N/A	RTV Silicone
601	Green	609	0.005	3000 psi	-65 to +300	10 min/24 hrs	764	Current PIN #609
609	Green		0.005	3000 psi	-65 to +300	10 min/24 hrs	764	General Purpose Retaining Compound
620	Green	640	0.015	3000 psi	-65 to +450	30 min/24 hrs	747	High Temperature Retaining Compound
635	Green	680	0.010	4000 psi	-65 to +300	1 hr/24 hrs	747	High Strength Retaining Compound
638	Green	680	0.015	4100 psi	-65 to +300	10 min/24 hrs	747	High Strength Retaining Compound
640	Green	620	0.007	3000 psi	-65 to +400	1 hr/24 hrs	747	High Temperature Retaining Compound
660	Silver		0.020	3000 psi	-65 to +300	20 min/24 hrs	764	Quick Metal
675	Green	609	0.005	3000 psi	-65 to +300	20 min/24 hrs	747	General Purpose Retaining Compound
680	Green	635	0.015	4000 psi	-65 to +300	10 min/24 hrs	747	High Strength Retaining Compound
706	Clear	755	N/A	N/A	N/A	N/A	N/A	Cleaning Solvent
707	Amber		N/A	N/A	N/A	N/A	N/A	Activator for Structural Adhesives
736	Amber		N/A	N/A	N/A	N/A	N/A	Primer NF
738	Amber		N/A	N/A	N/A	N/A	N/A	Depend Activator
747	Yellow	N/A	N/A	N/A	N/A	N/A	N/A	Primer T
751	Clear		N/A	N/A	N/A	N/A	N/A	Activator for Structural Adhesives
755	Clear		N/A	N/A	N/A	N/A	N/A	Cleaning Solvent
764	Green		N/A	N/A	N/A	N/A	N/A	Primer N
767	Silver		N/A	N/A	-65 to +1600	N/A	N/A	Anti-Seize Lubricant

# Section

# 1

**GENERAL**

**How it Works**

It's a preview. You can download the full file by clicking the link below.

<https://shopservicemanual.com/>

Service Manuals from 2\$