

MX150 and MX170 Tractors

Service Manual Don 7-87886

Table of Contents

Binder 1 Contains Tabs 1 to 6
Binder 2 Contains Tabs 7 to 10

	Section	Pub. No.
1 GENERAL		
Loctite Product Chart		8-98902
Standard Torque Specifications	1000	7-68610
Safety Rules, General Information and Torque Specifications.....	1001	7-65920
General Specifications and Torques	1002	7-92570
Special Tools.....	1005	7-10700
2 ENGINE		
Engine Removal	2001	7-10710
NOTE: For Service and Overhaul procedures refer to your Engine Service Manual.		
3 FUEL SYSTEM		
Fuel Tank	3005	7-10720
NOTE: For Service and Overhaul procedures refer to your Engine Service Manual.		
4 ELECTRICAL		
How it Works (Not Available).....	4	7-10730
Electrical Troubleshooting and Schematics (Not Available).....	4001	7-10740
Instrument Cluster Programming	4002	7-71332
Battery Servicing and Testing	4004	7-73210
Alternator.....	4008	7-68501
Electrical Schematic Poster		7-90380
5 STEERING		
How It Works	5	7-72230
Steering Column and Steering Hand Pump	5001	7-10780
Rexroth Steering Hand Pump	5002	7-73960
Danfoss Steering Hand Pump.....	5002	7-73341
Eaton Steering Hand Pump.....	5002	7-73351
6 TRANSMISSION		
Engine and Speed Transmission Split	6002	7-10801
SeedTransmission and Range transmission Split.....	6003	7-10811
Transmission Input Drive Shaft and Torque Dampener.....	6004	7-66080
Servicing the Powershift Transmission	6006	7-10831
Servicing the Range Transmission	6007	7-10841
Powershift Valve.....	6009	7-66131
Shuttle Valve	6010	7-10860
Differential and Differential Lock	6012	7-10880
MFD Drive Shaft.....	6014	7-66170

continued

NOTE: Information contained in this Manual may cover features that are not available in all markets worldwide.

CASE CORPORATION
700 State Street
Racine, WI 53404 U.S.A.

CASE CANADA CORPORATION
3350 South Service Road
Burlington, ON L7N 3M6 CANADA

Don 7-14326

Copyright © 2000 Case Corporation
Printed in U.S.A.
March 2000 (Revised October 2000)

MFD Output Shaft and Bearing.....	6015	7-67821
MFD Clutch	6017	7-10921
Rear Axles and Planetaries	6018	7-10930
PTO	6019	7-10941
MFD Axle	6021	7-10950
PTO Front Drive Shaft and Hydraulic Pump Drive Gear.....	6023	7-10960
7 BRAKES		
How It Works.....	7	7-10971
Parking Brake	7001	7-10981
Service Brakes.....	7002	7-10991
Hydraulic Trailer Brake Valve	7004	7-67711
8 HYDRAULICS		
How it Works.....	8	7-11010
How to Read Hydraulic Schematics.....	8000	8-94372
Hydraulic Troubleshooting and Schematic	8001	7-11031
Charge Pump/Transfer Pump	8003	7-11041
Hydraulic Valves	8006	7-11060
Front Hitch	8007	7-73240
Rear Hitch	8010	7-11080
Hydraulic Schematic Poster.....		7-90390
9 CHASSIS AND MOUNTED EQUIPMENT		
Pedal, Lever Adjustments	9001	7-11090
Air Conditioner Troubleshooting (Visual and Operating)	9002	7-85050
Air Conditioner Gauges and Testing.....	9003	7-85060
Air Conditioner System Service (Refrigerant Recovery, System Evacuation and Recharging)	9004	7-85070
Air Conditioner System Components Service.....	9005	7-85080
Cab Removal and Tilting the Cab Roof	9006	7-11140
10 CONTROLLER SYSTEMS		
Hitch/MFD/Differential Lock Controller Calibration, Error Codes Troubleshooting and Schematics	10002	7-73582
Independent Front Suspension Axle Calibration, Error Codes, Troubleshooting and Schematics.....	10003	7-73900
PTO/FNR Controller and Powershift Configuration, Error Codes and Schematics	10006	7-73591
Programming the PTO/FNR Controller and Hitch/MFD/Differential Lock Controller.....	10010	7-74001

LOCTITE PRODUCT CHART

Product	Color	Similar Products	Gap (In Inches)	Strength (Steel/Steel)	Working Temperature Range-Fahrenheit	Fixture/Full Cure (Steel/Steel) Time	Primer	Description
#3	Dark Brown					24 hr	N/A	Form a Gasket (works with oil, fuel or grease) Pliable
80	Yellow					Fast	N/A	Weatherstrip Adhesive
123	Clear					N/A	N/A	Parts Cleaner Fluid
220	Blue	290	0.003	57/143 in lbs	-65 to +250	6 min/24 hrs	747	Wicking Threadlocker
221	Purple	222	0.005	75/44 in lbs	-65 to +300	2 min/24 hrs	747	Low Strength Threadlocker
222	Purple		0.005	53/30 in lbs	-65 to +300	20 min/24 hrs	764	Low Strength Threadlocker (Small Screws)
225	Brown	222	0.010	45/25 in lbs	-65 to +300	7 min/24 hrs	747	Low Strength Threadlocker
242	Blue		0.005	80/50 in lbs	-65 to +300	10 min/24 hrs	764	Medium Strength Threadlocker
262	Red	271	0.005	160/190 in lbs	-65 to +300	5 min/24 hrs	747	High Strength Threadlocker
270	Green	271	0.007	160/320 in lbs	-65 to +300	3 min/24 hrs	747	High Strength Threadlocker
271	Red	262	0.007	160/320 in lbs	-65 to +300	10 min/24 hrs	764	High Strength Threadlocker
272	Red	620	0.007	180/220 in lbs	-65 to +450	30 min/24 hrs	764	High Temperature, High Strength
275	Green	277	0.010	210/300 in lbs	-65 to +300	3 min/24 hrs	747	High Strength Threadlocker
277	Red		0.010	225/300 in lbs	-65 to +300	60 min/24 hrs	764	High Strength Threadlocker
290	Green		0.003	85/350 in lbs	-65 to +300	6 min/24 hrs	764	Wicking Threadlocker
*404	Clear	495	0.006	3200 psi	-65 to +180	30 sec/24 hrs	N/A	Instant Adhesive
*406	Clear		0.004	3200 psi	-65 to +180	15 sec/24 hrs	N/A	Surface Insensitive Adhesive
*409	Clear	454	0.008	2500 psi	-65 to +180	50 sec/24 hrs	N/A	Gel Instant Adhesive
*414	Clear		0.006	2500 psi	-65 to +180	30 sec/24 hr	N/A	Instant Adhesive
*415	Clear	454	0.010	2500 psi	-65 to +180	50 sec/24 hrs	N/A	Gap Filling Instant Adhesive (Metals)
*416	Clear	454	0.010	2500 psi	-65 to +180	50 sec/24 hrs	N/A	Gap Filling Instant Adhesive (Plastics)
*420	Clear		0.002	2500 psi	-65 to +180	15 sec/24 hrs	N/A	Wicking Instant Adhesive
*422	Clear	454	0.020	2800 psi	-65 to +180	60 sec/24 hrs	N/A	Gap Filling Instant Adhesive
*430	Clear		0.005	2500 psi	-65 to +180	20 sec/24 hrs	N/A	Metal Bonding Adhesive
*445	White/Black		0.250	2000 psi	-65 to +180	5 min/24 hrs	N/A	Fast Setting 2 Part Epoxy
*454	Clear		0.010	3200 psi	-65 to +180	15 sec/24 hrs	N/A	Surface Insensitive Gen Instant Adhesive
*495	Clear		0.004	2500 psi	-65 to +180	20 sec/24 hrs	N/A	General Purpose Instant Adhesive
*496	Clear		0.005	2500 psi	-65 to +180	20 sec/24 hrs	N/A	Metal Bonding Adhesive
504	Brt Orange	515	0.030	750 psi	-65 to +300	90 min/24 hrs	None	Rigid Gasket Eliminator
509	Light Blue		0.020	750 psi	-65 to +320	6 hr/72 hrs	764	Flange Sealant
510	Red		0.020	1000 psi	-65 to +400	30 min/24 hrs	764	High Temperature, Gasket Eliminator
515	Purple		0.010	750 psi	-65 to +300	1 hr/24 hrs	764	Gasket Eliminator 515

LOCTITE PRODUCT CHART

Product	Color	Similar Products	Gap (In Inches)	Strength (Steel/Steel)	Working Temperature Range-Fahrenheit	Fixture/Full Cure (Steel/Steel) Time	Primer	Description
518	Red	515	0.030	500psi	-65 to +300	1hr/24 hrs	764	Gasket Eliminator 518 for Aluminum
542	Brown	569	N/A	132/92 in lbs	-65 to +300	2 hr/24 hrs	747	Hydraulic Sealant
545	Purple		N/A	25/20 in lbs	-65 to +300	4 hr/24 hrs	747	Low Strength Pneumatic/Hydraulic Sealant
549	Orange	504	0.020	2500 psi	-65 to +300	2 hr/24 hrs	747	Instant Seal Plastic Gasket
554	Red	277	0.015	240/240 in lbs	-65 to +300	2 to 4 hrs/24 hrs	764	Refrigerant Sealant
567	White	592	N/A	500 psi	-65 to +400	4 hrs/24 hrs	764	Pipe Sealant for Stainless Steel
568	Orange	277	0.015	2500 psi	-65 to +300	12 hrs/24 hrs	764	Plastic Gasket
569	Brown	545	0.010	40/25 in lbs	-65 to +300	1 hr/24 hrs	764	Hydraulic Sealant
570	Brown	592	N/A	25/40 in lbs	-65 to +300	6 hrs/72 hrs	764	Steam Sealant
571	Brown	592	0.015	40/20 in lbs	-65 to +300	2 to 4 hrs/24 hrs	764	Pipe Sealant
572	White	578.575	N/A	80/27 in lbs	-65 to +300	24 hrs/72 hrs	None	Gasketing
592	White		0.020	500 psi	-65 to +400	4 hrs/72 hrs	736	Pipe Sealant with Teflon
593	Black		0.250	400 psi	-95 to +400	30 min/24 hrs	N/A	RTV Silicone
601	Green	609	0.005	3000 psi	-65 to +300	10 min/24 hrs	764	Current PIN #609
609	Green		0.005	3000 psi	-65 to +300	10 min/24 hrs	764	General Purpose Retaining Compound
620	Green	640	0.015	3000 psi	-65 to +450	30 min/24 hrs	747	High Temperature Retaining Compound
635	Green	680	0.010	4000 psi	-65 to +300	1 hr/24 hrs	747	High Strength Retaining Compound
638	Green	680	0.015	4100 psi	-65 to +300	10 min/24 hrs	747	High Strength Retaining Compound
640	Green	620	0.007	3000 psi	-65 to +400	1 hr/24 hrs	747	High Temperature Retaining Compound
660	Silver		0.020	3000 psi	-65 to +300	20 min/24 hrs	764	Quick Metal
675	Green	609	0.005	3000 psi	-65 to +300	20 min/24 hrs	747	General Purpose Retaining Compound
680	Green	635	0.015	4000 psi	-65 to +300	10 min/24 hrs	747	High Strength Retaining Compound
706	Clear	755	N/A	N/A	N/A	N/A	N/A	Cleaning Solvent
707	Amber		N/A	N/A	N/A	N/A	N/A	Activator for Structural Adhesives
736	Amber		N/A	N/A	N/A	N/A	N/A	Primer NF
738	Amber		N/A	N/A	N/A	N/A	N/A	Depend Activator
747	Yellow	N/A	N/A	N/A	N/A	N/A	N/A	Primer T
751	Clear		N/A	N/A	N/A	N/A	N/A	Activator for Structural Adhesives
755	Clear		N/A	N/A	N/A	N/A	N/A	Cleaning Solvent
764	Green		N/A	N/A	N/A	N/A	N/A	Primer N
767	Silver		N/A	N/A	-65 to +1600	N/A	N/A	Anti-Seize Lubricant

Section 1000

STANDARD TORQUE SPECIFICATIONS

CASE CORPORATION
700 State Street
Racine, WI 53404 U.S.A.

CASE CANADA CORPORATION
450 Sherman Avenue
Hamilton, ON L8N 4C4 CANADA

Rac 7-68610

© 1997 Case Corporation
Printed in U.S.A.
May, 1997

1000

It's a preview. You can download the full file by clicking the link below.

<https://shopservicemanual.com/>

Service Manuals from 2\$