Service Manual



JCB 7000 Series Fastrac

Section 1 - General Information

Section 2 - Care and Safety

Section 3 - Maintenance

Section A - Optional Equipment

Section B - Body and Framework

Section C - Electrics

Section D - Controls

Section E - Hydraulics

Section F - Transmission

Section G - Brakes

Section H - Steering

Section S - Suspension

Section T - Engine



Publication No. **9803/8060-3**



World Class Customer Support

Section 1



General Information

Service Manual - JCB 7000 Series Fastrac

Section 1 - General Information

Section 2 - Care and Safety

Section 3 - Maintenance

Section A - Optional Equipment

Section B - Body and Framework

Section C - Electrics

Section D - Controls

Section E - Hydraulics

Section F - Transmission

Section G - Brakes

Section H - Section H

Section S - Suspension

Section T - Engine



Publication No. **9803/8060-3**



World Class Customer Support



Section 1 - General Informtion

Notes:			
			•
		_	•

1-0 9803/8060-3 **1-0**



Section 1 - General Informtion

Contents	Page No.
Introduction	
About This Manual	1-1
Machine Model and Serial Number	1-1
Using the Service Manual	1-1
Units of Measurement	1-1
Section Numbering	1-1
Identifying your Machine	
Machine Identification Plate	1-2
Component Identification Plates	1-3
Chandard Tarries Cattings	
Standard Torque Settings	1.6
Zinc Plated Fasteners and Dacromet Fasteners	
Introduction	
Zinc Plated Fasteners (golden finish)	
Dacromet Fasteners (mottled silver finish)	
Hydraulic Connections	
'O' Ring Face Seal System	
'Torque Stop' Hose System	1-12
Special Tools	
Numerical List	1-13
Tool Detail Reference	
Section B - Body and Framework	
Section C - Electrics	
Section E - Hydraulics	
Section F - Transmission	1-32
Section G - Brakes	1-32
Section S - Suspension	1-32
Service Consumables	
Sealing and Retaining Compounds	1-38

1-i 1-i



Section 1 - General Informtion

Contents Page No.

1-ii 1-ii

It's a preview. You can download the full file by clicking the link below.

https://shopservicemanual.com/

Service Manuals from 2\$