SHOP

KOMATSU

PW05-1

MACHINE MODEL SERIAL No.

PW05-1

1001 and up

CONTENTS

	No. of	page
10	STRUCTURE AND FUNCTION	10-1
20	TESTING AND ADJUSTING	20-1
30	DISASSEMBLY AND ASSEMBLY	30-1
40	MAINTENANCE STANDARD	40-1

The affected pages are indicated by the use of the following marks. It is requested that necessary actions be taken to these pages according to the table below.

Mark	Indication	Action required
0	Page to be newly added	Add
•	Page to be replaced	Replace
()	Page to be deleted	Discard

Pages having no marks are those previously revised or made additions.

LIST OF REVISED PAGES

					LIS I	Ur	NE VI	ו עםכ	AGE	:5				
Mark	Page	Revision number	Mark	Page	Revision number	Mark	Page	Revision number	Mark	Page	Revision number	Mark	Page	Revision number
•	00-1	1		10-29		0	20-31	1	0	30-34	(i)			
	00-2	1		10-30		0	20-32	1	0	30-35				
0	00-2-1	1		10-32		0	20-33	(I)	0	30-36				
	00-3			10-33		0	20-34	1	0	30-37	1			
	00-4			10-34		0	20-35	1	0	30-38	(i)			
	00-5			10-35		0	20-36	1	0	30-39	(i)	ĺ		
	00-6			10-36					0	30-40	(i)			
	00-7			10-37		0	30-1	1	0	30-41	(i)			
	8-00					0	30-2	1						
	00-9		0	20-1	(i)	0	30-3	1		40-1				
	00-10		0	20-2	(i)	0	30-4	(I)		40-2				
	00-11		0	20-3	(i)	0	30-5	(I)		40-3				
	00-12		0	20-4	1	0	30-6	1		40-4				
			0	20-5	1	0	30-7	1		40-5				
	10-1		0	20-6	1	0	30-8	1		40-6				
	10-2		0	20-7	(i)	0	30-9	1		40-7				
	10-3		0	20-8	1	0	30-10	1		40-8				
	10-4		0	20-9	1	0	30-11	1		40-10				
	10-5		0	20-10	(i)	0	30-12	1		40-11				
	10-6		0	20-11	1	0	30-13	1		40-12				
	10-7		0	20-12	<u>(1)</u>	0	30-14	1		40-13				
	10-8		0	20-13	1	0	30-15	1		40-14				
	10-9		0	20-13	①	0	30-16	1		40-15				
	10-10					0	30-17	1						
	10-11		0	20-15	1	0	30-18	1						
	10-12		0	20-16	①	0	30-19	1						
	10-13		0	20-17	1	0	30-20	(I)						
	10-15		0	20-19	1)	0	30-21	1						
	10-17		0	20-20	1	0	30-22 30-23	(I) (I)						
	10-19		0	20-21	1	0	30-23	(i)						
	10-20		0	20-22	1	0	30-25	(i)						
	10-21		0	20-23	1	0	30-26	(i)						
	10-22		0	20-24	1	0	30-27	(I)						
	10-23		0	20-25	1	0	30-28	(I)						
	10-24		0	20-26	1	0	30-29	(I)						
	10-25		0	20-27	1	0	30-30	1						
	10-26		0	20-28	1	0	30-31	①						
	10-27		0	20-29	1	0	30-32	1						
	10-28		0	20-30	1	0	30-33	1)						

IMPORTANT SAFETY NOTICE

Proper service and repair is extremely important for the safe operation of your machine. The service and repair techniques recommended by Komatsu and described in this manual are both effective and safe methods of operation. Some of these operations require the use of tools specially designed by Komatsu for the purpose.

To prevent injury to workers, the symbols A and A are used to mark safety precautions in this manual. The cautions accompanying these symbols should always be followed carefully. If any dangerous situation arises or may possibly arise, first consider safety, and take the necessary actions to deal with the situation.

A SAFETY

GENERAL PRECAUTIONS

Mistakes in operation are extremely dangerous. Read the Operation and Maintenance Manual carefully BEFORE operating the machine.

- 1. Before carrying out any greasing or repairs. read all the precautions given on the decals which are fixed to the machine.
- 2. When carrying out any operation, always wear safety shoes and helmet. Do not wear loose work clothes, or clothes with buttons missing.
 - · Always wear safety glasses when hitting parts with a hammer.
 - Always wear safety glasses when grinding parts with a grinder, etc.
- 3. If welding repairs are needed, always have a trained, experienced welder carry out the work. When carrying out welding work, always wear welding gloves, apron, glasses, cap and other clothes suited for welding work.
- 4. When carrying out any operation with two or more workers, always agree on the operating procedure before starting. Always inform your fellow workers before starting any step of the operation. Before starting work, hang UNDER REPAIR signs on the controls in the operator's compartment.
- 5. Keep all tools in good condition and learn the correct way to use them.

6. Decide a place in the repair workshop to keep tools and removed parts. Always keep the tools and parts in their correct places. Always keep the work area clean and make sure that there is no dirt or oil on the floor. Smoke only in the areas provided for smoking. Never smoke while working.

PREPARATIONS FOR WORK

- 7. Before adding oil or making any repairs. park the machine on hard, level ground, and block the wheels or tracks to prevent the machine from moving.
- 8. Before starting work, lower blade, ripper. bucket or any other work equipment to the ground. If this is not possible, insert the safety pin or use blocks to prevent the work equipment from falling. In addition, be sure to lock all the control levers and hang warning signs on them.
- 9. When disassembling or assembling, support the machine with blocks, jacks or stands before starting work.
- 10. Remove all mud and oil from the steps or other places used to get on and off the machine. Always use the handrails, ladders or steps when getting on or off the machine. Never jump on or off the machine. If it is impossible to use the handrails, ladders or steps, use a stand to provide safe footing.

PRECAUTIONS DURING WORK

11. When removing the oil filler cap, drain plug or hydraulic pressure measuring plugs, loosen them slowly to prevent the oil from spurting out.

Before disconnecting or removing components of the oil, water or air circuits, first remove the pressure completely from the circuit.

12. The water and oil in the circuits are hot when the engine is stopped, so be careful not to get burned.

Wait for the oil and water to cool before carrying out any work on the oil or water circuits.

- 13. Before starting work, remove the leads from the battery. Always remove the lead from the negative (—) terminal first.
- 14. When raising heavy components, use a hoist or crane.

Check that the wire rope, chains and hooks are free from damage.

Always use lifting equipment which has ample capacity.

Install the lifting equipment at the correct places. Use a hoist or crane and operate slowly to prevent the component from hitting any other part. Do not work with any part still raised by the hoist or crane.

- 15. When removing covers which are under internal pressure or under pressure from a spring, always leave two bolts in position on opposite sides. Slowly release the pressure, then slowly loosen the bolts to remove.
- 16. When removing components, be careful not to break or damage the wiring. Damaged wiring may cause electrical fires.
- 17. When removing piping, stop the fuel or oil from spilling out. If any fuel or oil drips on to the floor, wipe it up immediately. Fuel or oil on the floor can cause you to slip, or can even start fires.
- 18. As a general rule, do not use gasoline to wash parts. In particular, use only the minimum of gasoline when washing electrical parts.

19. Be sure to assemble all parts again in their original places.

Replace any damaged parts with new parts.

- When installing hoses and wires, be sure that they will not be damaged by contact with other parts when the machine is being operated.
- 20. When installing high pressure hoses, make sure that they are not twisted. Damaged tubes are dangerous, so be extremely careful when installing tubes for high pressure circuits. Also, check that connecting parts are correctly installed.
- 21. When assembling or installing parts, always use the specified tightening torques. When installing protective parts such as guards, or parts which vibrate violently or rotate at high speed, be particularly careful to check that they are installed correctly.
- 22. When aligning two holes, never insert your fingers or hand. Be careful not to get your fingers caught in a hole.
- 23. When measuring hydraulic pressure, check that the measuring tool is correctly assembled before taking any measurements.
- 24. Take care when removing or installing the tracks of track-type machines.

When removing the track, the track separates suddenly, so never let anyone stand at either end of the track.

It's a preview. You can download the full file by clicking the link below.

https://shopservicemanual.com/

Service Manuals from 2\$