

2008 FLT Police Models Service Manual Supplement

©2007 H-D.
ALL RIGHTS RESERVED
99483-08SP

Printed in the U.S.A.

VISIT THE HARLEY-DAVIDSON WEB SITE http://www.harley-davidson.com

ABOUT THIS MANUAL

GENERAL

This Service Manual Supplement has been designed to be used with the current Service Manual and has been prepared with two purposes in mind. First, it will acquaint the user with the construction of the Harley-Davidson product and assist in the performance of basic maintenance and repair. Secondly, it will introduce to the professional Harley-Davidson Technician the latest field-tested and factory-approved major repair methods. We sincerely believe that this Service Manual Supplement will make your association with Harley-Davidson products more pleasant and profitable.

NOTE

This Service Manual Supplement provides information unique to this model motorcycle. Any information not presented in this supplement can be found in the appropriate Service Manual or Electrical Diagnostic Manual.

HOW TO USE YOUR SERVICE MANUAL SUPPLEMENT

Use the TABLE OF CONTENTS (which follows this FORE-WORD) and the INDEX (at the back of this manual) to quickly locate subjects. Sections and topics in this manual are sequentially numbered for easy navigation.

NO.	CHAPTER
1	Maintenance
2	Chassis
3	Engine
4	Fuel System
5	Electric Starter
6	Drive
7	Transmission
8	Electrical
А	Appendix A Wiring
В	Appendix B Glossary

For example, a cross-reference shown as **2.1 SPECIFICA-TIONS** refers to chapter 2 CHASSIS, heading 2.1 SPECIFICATIONS.

If the subject you seek is not in this supplement, refer to the corresponding section in the appropriate Service Manual. Check the title page located in the front of each section to find the subject.

For quick and easy reference, all pages contain a section number followed by a page number. For example, page 3-5 refers to page 5 in section 3.

In figure legends, the number following the name of a part indicates the quantity necessary for one complete assembly.

PREPARATION FOR SERVICE

AWARNING

Stop the engine when refueling or servicing the fuel system. Do not smoke or allow open flame or sparks near gasoline. Gasoline is extremely flammable and highly explosive, which could result in death or serious injury. (00002a)

Good preparation is very important for efficient service work. A clean work area at the start of each job will allow you to perform the repair as easily and quickly as possible, and will reduce the incidence of misplaced tools and parts. A motorcycle that is excessively dirty should be cleaned before work starts. Cleaning will occasionally uncover sources of trouble. Tools, instruments and any parts needed for the job should be gathered before work is started. Interrupting a job to locate tools or parts is a distraction and causes needless delay.

NOTES

- To avoid unnecessary disassembly, carefully read all relative service information before repair work is started.
- In figure legends, the number which follows the name of a part indicates the quantity necessary for one complete assembly.
- When servicing a vehicle equipped with the Harley-Davidson Smart Security System (H-DSSS), you must first disarm the security system. Either keep the fob in close proximity to the vehicle, or use Digital Technician to disable the security system while the vehicle is being serviced and re-enable the system after service is completed.

SERVICE BULLETINS

In addition to the information presented in this Service Manual Supplement and the appropriate Service Manual, Harley-Davidson Motor Company will periodically issue Service Bulletins to Harley-Davidson dealers. Service Bulletins cover interim engineering changes and supplementary information. Consult the Service Bulletins to keep your product knowledge current and complete.

USE GENUINE REPLACEMENT PARTS

WARNING

Do not use aftermarket parts and custom made front forks which can adversely affect performance and handling. Removing or altering factory installed parts can adversely affect performance and could result in death or serious injury. (00001a)

To ensure satisfactory and lasting repairs, carefully follow the Service Manual instructions and use only genuine Harley-Davidson replacement parts. Behind the emblem bearing the words GENUINE HARLEY-DAVIDSON stand more than 100 years of design, research, manufacturing, testing and inspecting experience. This is your assurance that the parts you are using will fit right, operate properly and last longer.

WARNINGS AND CAUTIONS

Statements in this service manual preceded by the following words are of special significance.

AWARNING

WARNING indicates a potentially hazardous situation which, if not avoided, could result in death or serious injury. (00119a)

ACAUTION

CAUTION indicates a potentially hazardous situation which, if not avoided, may result in minor or moderate injury. (00139a)

CAUTION

CAUTION used without the safety alert symbol indicates a potentially hazardous situation which, if not avoided, may result in property damage. (00140a)

NOTE

Refers to important information, and is placed in italic type. It is recommended that you take special notice of these items.

Proper service and repair is important for the safe, reliable operation of all mechanical products. The service procedures recommended and described in this service manual are effective methods for performing service operations.

AWARNING

Always wear proper eye protection when using hammers, arbor or hydraulic presses, gear pullers, spring compressors, slide hammers and similar tools. Flying parts could result in death or serious injury. (00496b)

Some of these service operations require the use of tools specially designed for the purpose. These special tools should be used when and as recommended. It is important to note that some warnings against the use of specific service methods, which could damage the motorcycle or render it unsafe, are stated in this service manual. However, please remember that these warnings are not all-inclusive. Inadequate safety precautions could result in death or serious injury.

Since Harley-Davidson could not possibly know, evaluate or advise the service trade of all possible ways in which service might be performed, or of the possible hazardous consequences of each method, we have not undertaken any such broad evaluation. Accordingly, anyone who uses a service procedure or tool which is not recommended by Harley-Davidson must first thoroughly satisfy himself that neither his nor the operator's safety will be jeopardized as a result. Failure to do so could result in death or serious injury.

PRODUCT REFERENCES

AWARNING

Read and follow warnings and directions on all products. Failure to follow warnings and directions can result in death or serious injury. (00470b)

When reference is made in this manual to a specific brand name product, tool or instrument, an equivalent product, tool or instrument may be substituted.

Kent-Moore Products

All tools mentioned in this manual with an "HD", "J" or "B" preface must be ordered through SPX Kent-Moore. For ordering information or product returns, warranty or otherwise, visit www.spx.com.

Loctite Sealing and Threadlocking Products

Some procedures in this manual call for the use of Loctite products. If you have any questions regarding Loctite product usage or retailer/wholesaler locations, please contact Loctite Corp. at www.loctite.com.

PRODUCT REGISTERED MARKS

Allen, Amp Multilock, Bluetooth, Brembo, Delphi, Deutsch, Dunlop, Dynojet, Fluke, G.E. Versilube, Gunk, Hydroseal, Hylomar, Kevlar, Lexan, Loctite, Lubriplate, Keps, K&N, Magnaflux, Marson Thread-Setter Tool Kit, MAXI fuse, Molex, MPZ, Mulitilock, Novus, Packard, Pirelli, Permatex, Philips, PJ1, Pozidriv, Robinair, S100, Sems, Snap-on, Teflon, Threadlocker, Torca, Torco, TORX, Tufoil, Tyco, Ultratorch, Velcro, X-Acto, and XM Satellite Radio are among the trademarks of their respective owners.

H-D MICHIGAN, INC. TRADEMARK INFORMATION

Harley, Harley-Davidson, H-D, Bar & Shield, Digital Tech, Digital Technician, Destroyer, Deuce, Dyna, Electra Glide, Evolution, Fat Boy, Glaze, Gloss, H-D, H-Dnet.com, HD, Harley, Heritage Softail, Heritage Springer, Low Rider, Night Rod, Night Train, Profile, Revolution, Road Glide, Road King, Rocker, Softail, Sportster, Sun Ray, Sunwash, Tech Link, Twin Cam 88, Twin Cam 88B, Twin Cam 96, Twin Cam 96B, Twin Cam 103, Twin Cam 103B, Twin Cam 110, Twin Cam 110B, Tour-Pak, Screamin' Eagle, Softail, Super Guide, Super Premium, SYN3, Ultra Glide, V-Rod, VRSC, Wide Glide, and Harley-Davidson Genuine Motor Parts and Genuine Motor Accessories are among the trademarks of H-D Michigan, Inc.

CONTENTS

All photographs, illustrations and procedures may not necessarily depict the most current model or component, but are based on the latest production information available at the time of publication.

Since product improvement is our continual goal, Harley-Davidson reserves the right to change specifications, equipment or designs at any time without notice and without incurring obligation.

MAINTENANCE		Manufacturing Tolerances	3-1
1.1 SCHEDULED MAINTENANCE	3.2 SERVICE WEAR LIMITS		
General	General3		
	1-1	3.3 OIL COOLER	
CHASSIS		Operation	3-3
2.4 SPECIFICATIONS, CHASSIS		Removal	
2.1 SPECIFICATIONS: CHASSIS	0.4	Cleaning and Inspection	
General		Oil Cooler Adapter and Thermostat Replacement	3-4
2.2 VEHICLE IDENTIFICATION NUMBI (V.I.N.)	ER	RemovalInstallation	
General	2-2	FUEL SYSTEM	
2.3 TIRES			
General	2.2	4.1 FUEL SYSTEM	
	2-3	No Unique Content	4-1
2.4 SEAT		ELECTRIC STARTER	
General			
Seat Installation		5.1 ELECTRIC STARTER	
Air Spring Replacement		No Unique Content	5-1
Removal		DRIVE	
InstallationSeat Bracket Mount Replacement		DRIVE	
Removal		6.1 DRIVE	
Installation			
2.5 AIR SEAT RESERVOIR		No Unique Content	6-1
Removal	2-8	TRANSMISSION	
Installation		- / ANOMICO (AN	
2 6 SADDI EDACS		7.1 TRANSMISSION	
2.6 SADDLEBAGS		No Unique Content	7-1
Lockset		ELECTRICAL	
Installation			
Lockset Catch		8.1 BULB CHART	
Removal		General	0.4
Installation			0-1
HingesRemoval		8.2 SYSTEM FUSES AND RELAYS	
Installation		System Fuses	8-3
Tether	2-12	Removal	8-3
Removal		Installation	8-4
Installation		8.3 REAR MARKER LIGHTS	
Tether Brackets			0.5
Installation		Marker Lights Replacement	
Knob and Spring Latch		Installation	
Removal			
Installation		8.4 HANDLEBAR SWITCHES	
Spring Latch Bracket		Horn and Siren Yelp Switch	8-6
RemovalInstallation		Removal	
		Installation	
2.7 TACHOMETER BRACKET: FLHP/E		Clutch Interlock Switch	
Removal	2-14	Installation	
Installation	2-15	Pursuit and Auxiliary Switch	8-8
ENGINE		Removal	
LINGINE		Installation	8-8
3.1 SPECIFICATIONS: ENGINE		8.5 AUTOMATIC COMPRESSION REI	LEASE
General	3-1	General	8-10
		Removal	8-10

TABLE OF CONTENTS

Installation	8-10	Wiring Diagrams	A-8
Compression Test	8-12	APPENDIX B GLOSSARY	
Diagnostic Tips Diagnostic Notes	8-12 8-12	B.1 GLOSSARY	
APPENDIX A WIRING		Acronyms and Abbreviations	B-1
A.1 CONNECTORS		REFERENCE MATERIAL	
Connectors	A-1	TOOLS	
A.2 INDEX TO WIRING DIAGRAMS		TORQUE VALUES	
Wiring Diagram Information		INDEX	V
Wiring Diagram Symbols	Δ-7		

It's a preview. You can download the full file by clicking the link below.

https://shopservicemanual.com/

Service Manuals from 2\$